



TC-C387N 8ARA-28 Bullet Camera

Wi-Fi Series



KEY FEATURES

- plastic housing
- Up to 4MP, 2560 × 1440 @ 12fps
- S+265/H265
- Color: 0.02Lux@ (F1.6, AGC ON), B/W: 0Lux with IR
- IR range up to 50m
- 1 × Built-in Mic, 1 × Built-in Loudspeaker
- Support microSD/microSDHC/microSDXC card, up to 256GB
- Operating conditions -10°C~50°C (-14°F~122°F), ≤95%RH
- DC5V, USB type-C, Charger Wattage > 10W
- IP65



Tiandy Technologies Co., Ltd



Tiandy Overseas



Tiandy



@tiandyofficial

Tiandy Technologies Co., Ltd.

Email: sales@tiandy.com

Website: en.tiandy.com

Tel: +86-22-58596065

Fax: +86-22-58596048

SPECIFICATIONS

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s-1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	DWDR
S/N	≥52dB
Lens	
Lens Type	Fixed focal lens
Focal Length	2.8mm
Lens Mount	M12
Aperture Range	F1.6
Aperture Type	Fixed
Field of View	94.5°(H); 52.0°(V); 108.9°(D)
Illuminator	
IR LEDs	4
IR Distance	Up to 50m
Wavelength	850nm
White LEDs	2
Whitelight Distance	Up to 30m
Red and Blue Alarm Flash	Yes
Compression Standard	
Video Compression	S+265/H265
Video Bit Rate	32k~2Mbps
Audio Compression	AAC/G.711A
Audio Sampling Rate	8kHz/16kHz
Image	
Max. Resolution	4MP,2560×1440@12fps
Main Stream	PAL:12fps(2560×1440)
Sub Stream	PAL:12fps(1280×720)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance

OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters; Adaptive character size; Lattice
Defog	Yes
Feature	
Exceptions Alarm	Disk Full; Disk R/W Error
Linkage Method	Trigger Sound; Trigger Recording; Trigger Capture
Video Analytics	Smart Alarm (human and vehicle detection)
Network	
Protocols	TCP/IP; ICMP; DNS; NTP; IPv4; SSH
Remote Connection	≤2
Client	Easy7 VMS; work with hey google; work with alexa; work with hey google; work with alexa
Mobile Client	EasyLive Plus
work with hey google	work with hey google
work with alexa	work with alexa
Wi-Fi	
Transmission Distance	Up tp 50m(based on actual environment)
Wireless Standard	IEEE802.11a/IEEE802.11b/ 802.11g/802.11n
Frequency Range	2.4G: 2.4 GHz ~ 2.4835 GHz 5G: 5.17 GHz~5.25 GHz, 5.735 GHz~5.835 GHz
Channel Bandwidth	20/40MHz
Wi-Fi Security	WPA-PSK/WPA2-PSK
Interface	
Built-in Mic	1× Built-in Mic
Built-in Speaker	1× Built-in Loudspeaker
Reset Button	Yes
On-board Storage	Support microSD/microSDHC/microSDXC card, up to 256GB
Bluetooth Provisioning	Yes
General	
Operating Temperature	-10°C~50°C(-14°F~122°F)
Operating Humidity	≤95%RH
Storage Temperature	-10°C~50°C(-14°F~122°F)
Storage Humidity	0~95%RH(non-condensing)
Power Supply	DC5V,USB type-C,Charger Wattage>10W
Protection	ESD6000V; IP65
Boundary Dimensions	219(L)117(W)162(H)mm
Package Dimensions	260(L)157(W)160(H)mm
GrossWeight	1.09kg
NetWeight	0.65kg

DIMENSIONS (Unit: mm)

