



TC-C349V 8ARA-4 Bullet Camera

Wi-Fi Series



KEY FEATURES

- Plastic housing
- Up to 400万,2560x1440@15fps
- S+265/H265
- Color:0.0005Lux @ (F1.0, AGC ON),B/W:0.0002Lux @ (F1.0, AGC ON); 0Lux with IR
- IR range up to 30m
- 1×Built-in Mic, 1×Built-in Loudspeaker
- Support microSD/microSDHC/microSDXC card,up to 256GB
- Operating conditions -5°C-50°C(23°F~122°F)), ≤95%RH
- DC5V,USB type-C,Charger Wattage≥10W



Tiandy Technologies Co.,Ltd



Tiandy Overseas



Tiandy



@tiandyofficial

Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com

Website: en.tiandy.com

Tel: +86-22-58596065

Fax: +86-22-58596048

SPECIFICATIONS

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.0005Lux @ (F1.0, AGC ON),B/W:0.0002Lux @(F1.0, AGC ON); 0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	WDR
S/N	≥52dB
Angle Adjustment	0~20°(T)
Lens	
Lens Type	Fixed focal lens
Focal Length	4mm
Lens Mount	M12
Aperture Range	F1.0
Aperture Type	Fixed
Field of View	86.4°(H); 48.6°(V); 98°(D)
Illuminator	
IR LEDs	2
IR Distance	Up to 30m
Wavelength	850nm
Compression Standard	
Video Compression	S+265/H265
Video Bit Rate	32k~2Mbps
Audio Compression	AAC/G.711A
Audio Sampling Rate	8K/16kHz
Image	
Max. Resolution	400万,2560x1440@15fps
Main Stream	PAL:15fps(2560×1440,1280×720)
Sub Stream	PAL:15fps(1280×720)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; Adaptive character size; Lattice
Defog	Yes

Feature	
Exceptions Alarm	Disk Full; Disk R/W Error
Linkage Method	Trigger Sound; Trigger Recording; Trigger Capture
Video Analytics	Smart Alarm(Human、 Vehicle)
Network	
Protocols	TCP/IP; ICMP; DNS; NTP; IPv4; SSH
Remote Connection	≤2
Client	Easy7 VMS; work with hey google; work with alexa; work with hey google; work with alexa
Mobile Client	EasyLive Plus
work with hey google	work with hey google
work with alexa	work with alexa
Wi-Fi	
Transmission Distance	Up tp 30m(based on actual environment)
Wireless Standard	IEEE802.11a/IEEE802.11b/ 802.11g/802.11n
Frequency Range	2.4G: 2.4 GHz ~ 2.4835 GHz 5G: 5.17 GHz~5.25 GHz, 5.735 GHz~5.835 GHz
Channel Bandwidth	20/40MHz
Wi-Fi Security	WPA-PSK/WPA2-PSK
Interface	
Built-in Mic	1× Built-in Mic
Built-in Speaker	1× Built-in Loudspeaker
Reset Button	Yes
On-board Storage	Support microSD/microSDHC/microSDXC card,up to 256GB
Bluetooth Provisioning	Yes
General	
Operating Temperature	-5°C-50°C(23°F~122°F))
Operating Humidity	≤95%RH
Storage Temperature	-5°C-50°C(23°F~122°F))
Storage Humidity	0~95%RH(non-condensing)
Power Supply	DC5V,USB type-C,Charger Wattage≥10W
Protection	ESD6000V
Boundary Dimensions	65(L)43(W)65(H)mm
Package Dimensions	92(L)92(W)107(H)mm
GrossWeight	0.371kg
NetWeight	0.171kg

DIMENSIONS (Unit: mm)

